

EN-35 S/D TOP COLD MIRROR TRN

Single lever cartridge
Standard 35mm

08EN35S4506



Technical specifications

Prescribed tightening torque ⁽¹⁾	10-12 Nm
Opening angle	23°
Rotation angle	93°
Working pressure (recommended)	1- 5 bar
Burst pressure	>50 bar
Life cycle	EN 817/NF077 U3 3 x ASME 112.18.1 M 3 x GB18145
	175.000 cycles 1.500.000 cycles 210.000 cycles
Sensitivity (r = 45 mm) ⁽²⁾	>12°
Fidelity ⁽²⁾	<5°
Max. Hot water recommended	60 - 65°C
Max. Hot water	90°C


Flow rate @ 3 bar ⁽²⁾

Free flow	27,40 l/min
A-Restrictor - Shower	12,60 l/min
Noise (NF077) - Rh-A, 3 bar	Group I ⁽²⁾


Operation Torque

Open - close	0,20 ÷ 0,40 Nm
Left-Right	0,20 ÷ 0,40 Nm

Flow rate at MIX ⁽²⁾



Sensitivity (at 3bar) ⁽²⁾




(1) The prescribed tightening torque is related to faucet body and nut both in brass material, pitch 1,5mm and no lubricant applied on the threads. For other faucet body - nut material combinations please contact SEDAL.


(2) Measured with SEDAL faucet.

Single lever cartridge
Standard 35mm
EN-35 S/D TOP COLD MIRROR TRN

Technical dimensions (3)



Machining prescription (4)



(3) Dimensions of the cartridge assembled into the faucet (without vertical gap between the cover and the base)
(4) Sealing surfaces must be free of burrs and sharp areas. The faucet body must be free of debris