

# FLEXIBLE HOSES

SEDAL's flexible hoses are manufactured according to the most demanding safety standards. 100% tested, flexible hoses are available in different combinations of materials and sizes



# FAUCET HOSES



FLEXIBLE HOSES FOR TAPS

DN6  
DN8



STANDARD FLEXIBLE HOSES

DN6  
DN8

CUSTOMIZABLE  
MATERIALS,  
LENGTHS AND  
FITTINGS

## Flexible hoses for faucets

Flexible hoses for sanitary faucet installations: taps, wash-basins, bidets.

Available as standard and under customer design and requirements of materials, length and fitting configuration.

## Materials

Stainless steel and nylon briding and PEX, SOFTPEX, EPDM tube options.

## Certifications

CSBAT, WRAS, AENOR, KIWA, DVGW and ACS.

### RECOMMENDED APPLICATIONS



#### WASHBASINS

Specially designed for washbasins.



#### BATH-SHOWER

Specially designed for bath showers.



#### KITCHEN

Suitable for use in kitchens.

# TECHNICAL SPECIFICATIONS

General	Flexible hoses for taps		Standard flexible hoses	
	DN6	DN8	DN6	DN8
End fittings	Brass		Brass CW614	
Nuts	3/8" - 1/2"		3/8" - 1/2"	
Nozzle	M-8/100 - M-10/100 18mm, 35mm, 50mm		-	
Sleeve	Stainless steel		Stainless steel AISI 304	
Hose	E.P.D.M. sanitary hose or PEX		E.P.D.M. sanitary hose or PEX	
Mesh	Mesh in stainless steel AISI 304 wire		Mesh in stainless steel AISI 304 wire	
Ø Internal diameter	6mm	8mm	6mm	8mm
Ø External diameter	10mm	12mm	10mm	12mm
Max. temperature	90°C	90°C	90°C	90°C
Drinking H <sub>2</sub> O	Yes	Yes	Yes	Yes
Burst pressure	100 kg/cm <sup>2</sup>	100 kg/cm <sup>2</sup>	100 kg/cm <sup>2</sup>	100 kg/cm <sup>2</sup>
Work pressure	25 kg/cm <sup>2</sup>	25 kg/cm <sup>2</sup>	25 kg/cm <sup>2</sup>	25 kg/cm <sup>2</sup>
Curvature radius	35mm	40mm	35mm	40mm
Nominal flow	20 l/min	25 l/min	20 l/min	25 l/min

# SANITARY HOSES



STANDARD FLEXIBLE HOSES

DN13  
DN19  
DN25



FLEXIBLE HOSES WITH ELBOW

DN8  
DN13  
DN19  
DN25

## Flexible hoses for sanitary water

Flexible hoses for sanitary installations: water heaters, water vessels, water storage tanks, solar water heaters and air conditioning.

Available as standard and under customer design and requirements of materials, length and fitting configuration.

## Certifications

Flexible hoses with elbow are CSBAT, WRAS, AENOR, KIWA, and ACS certified.

### RECOMMENDED APPLICATIONS



#### WATER HEATERS

Designed for heaters, storage tanks, vessels.



#### TOILETS

Specially designed for toilets.

# TECHNICAL SPECIFICATIONS

General	Standard flexible hoses			Flexible hoses with elbow			
	DN13	DN19	DN25	DN8	DN13	DN19	DN25
Model	Brass			Brass and brass elbow			
End fittings	Brass			Brass and brass elbow			
Nuts	1/2" - 3/4"	3/4" - 1"	3/4" - 1"	3/8" - 1/2"	1/2-3/4"	3/4"	1"
Sleeve	Stainless steel			Stainless steel AISI 304			
Hose	E.P.D.M. sanitary hose			E.P.D.M. sanitary hose			
Mesh	Mesh in stainless steel AISI 304 wire			Mesh in stainless steel AISI 304 wire			
Ø Internal diameter	13mm	19mm	25mm	8mm	13mm	19mm	25mm
Ø External diameter	19mm	27mm	33mm	12mm	19mm	27mm	33mm
Max. temperature	90°C	90°C	90°C	90°C	90°C	90°C	90°C
Drinking H <sub>2</sub> O	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Burst pressure	90 kg/cm <sup>2</sup>	90 kg/cm <sup>2</sup>	90 kg/cm <sup>2</sup>	100 kg/cm <sup>2</sup>	80 kg/cm <sup>2</sup>	60 kg/cm <sup>2</sup>	35 kg/cm <sup>2</sup>
Work pressure	15 kg/cm <sup>2</sup>	10 kg/cm <sup>2</sup>	10 kg/cm <sup>2</sup>	25 kg/cm <sup>2</sup>	20 kg/cm <sup>2</sup>	15 kg/cm <sup>2</sup>	15 kg/cm <sup>2</sup>
Curvature radius	50mm	70mm	100mm	40mm	45mm	40mm	40mm
Nominal flow	70 l/min	120 l/min	200 l/min	25 l/min	65 l/min	120 l/min	200 l/min



**sedal**  
THE FAUCET'S HEART

SEDAL GROUP  
Polígono Industrial Can Sunyer · C/Química, 2-12  
E-08740 Sant Andreu de la Barca (Barcelona) · Spain  
Tel. +34 93 680 33 00 · Fax +34 93 680 33 03  
[sedal@sedal.com](mailto:sedal@sedal.com) · [www.sedal.com](http://www.sedal.com)



Get access to the complete and  
latest product technical data!